DIAMOND CUT 3000



This product is part of **REFINISH**





Description:

Cartec Diamond Cut 3000 is a compound with exceptional deep cutting, making it the perfect choice for weathered, hard and scratch-resistant paints. It quickly and effortlessly removes deep scratches, sanding marks (P1500 and above), spray mist, orange peel, dust, chips and runners (for severe imperfections, using sandpaper beforehand can increase efficiency).

Product benefits:

- ✓ Fast and deep cutting
- ✓ Time-saving
- ✓ Easy to buff off
- ✓ Provides instant high gloss
- ✓ Free of silicones, ammonia and fillers

Application:

Cartec Diamond Cut 3000 can be used for deep (sanding) scratches, overspray, orange peel, dust, sags and runners.

Instructions for use:

- 1. Determine the working surface within shoulder width and six times the area of the polishing pad.
- 2. Apply 3 pea-sized dots (for Ø150mm) of Cartec Diamond Cut 3000 to the polishing pad.
- 3. Rotary: take the Cartec green pad for rotary machines (RF2110 for Ø150mm). Spread the product on the lowest setting and increase the speed to 1500 rpm.
 - Dual Action: Take the Cartec green pad for dual action machines (RF2116 for \varnothing 150mm). Spread the product on the lowest setting and increase the speed to 3500 rpm.
- 4. Work in sections while applying even pressure. Continue until the scratches are removed.
- 5. Clean the surface thoroughly with the Cartec Microfibre Cloth Green (RF2203C) to remove all polish residue.

Tips & Tricks:

- ✓ Use Cartec Panel Spray (REFLSP) to completely degrease the surface, remove remaining polish residue and review the actual condition of the paintwork.
- When using a rotary polisher, do not keep polishing in the same spot for too long to avoid overheating the paintwork.

Required items:







Scan or click <u>here</u> for the overview with all matching polishing pads



RF2203C

Item codes:

ITEM CODE	CONTENT
REFL30-015	150 ml
REFL30-1	1 L