TECHNICAL DATASHEET

COMPOUND 5000





INGENIOUS CAR CARE

This product is part of **REFINISH**

Description:

Cartec Compound 5000 is an effective polishing compound for removing scratches, oxidation, discoloration, and other imperfections in car paint.

Product benefits:

- Effective scratch removal and other imperfections
- ✓ Suitable for freshly painted surfaces
- ✓ Economical choice
- Produces minimal dust
- ✓ Non-greasy
- ✓ Free from silicones, ammonia, and fillers

Application:

Cartec Compound 5000 is suitable for use on dull car paint, scratches, and oxidation.

Instructions for use:

- 1. Identify the work area within shoulder width and six times the surface area of the polishing pad.
- Apply 3 pea-sized dots (for ⊘150mm) of Cartec Compound 5000 to the polishing pad
- Rotary: Use the Cartec yellow pad for rotary machines (RF2120 for ∞150mm). Spread the product at the lowest speed and gradually increase the speed to 1500 RPM.

• Dual Action: Use the Cartec yellow pad for orbital machines (RF2126 for @150mm). Spread the product at the lowest speed and gradually increase the speed to 3500 RPM.

- 4. Work in sections while applying even pressure. Process the product until the scratches are removed.
- 5. Thoroughly clean the surface with the Cartec Microfiber Cloth Yellow (RF2205C) to remove all polishing residue.

Tips & Tricks:

- ✓ Use Cartec Panel Spray (REFLSP) to completely degrease the surface, remove remaining polish residue and review the actual condition of the paintwork.
- When using a rotary polishing machine, avoid polishing in one spot for too long to prevent overheating of the paint.

Required items:







Cartec Rotary Polishing Machine (3096/40) / Cartec Dual Action Polishing Machine (3096/60)

Scan or click <u>here</u> for the overview with all matching polishing pads

RF2205C

Item codes:

	CONTENT
REFL50-015	150 ml
REFL50-1	1 L