# **TECHNICAL DATASHEET**

WET & PROTECT







## **Description:**

Cartec Wet & Protect is a hydrophobic spray coating that can be easily applied after washing the car. The product gives the car paint a very deep gloss and provides extreme water beading.

## **Product benefits:**

- Quick to apply spraycoating
- ✓ Makes surfaces water-repellent in a very short time
- Gives extremely high contact angle to water and raindrops
- ✓ Leaves a protective film on the treated surface
- ✓ Highly resistant to acid and alkaline chemicals
- ✓ Works well on paintwork, vinyl, PPF and rims

## **Application:**

Cartec Wet & Protect is a "spray & rinse" coating that adheres strongly to the surface after the car has been washed and rinsed. By applying the product to the wet car, Cartec Wet & Protect will spread well and can adhere to the paintwork. Upon rinsing, a very good protective coating, extra deep gloss and a strong water-repellent effect is created which is immediately visible.

#### Directions for use:

Required pre-treatment:

- 1. Clean the car with Cartec Twister Comfort (1407) and then rinse the car well with a pressure washer.
- 2. Then wash the whole car with Cartec Cherry Wash (1208). Rinse the shampoo off with clean water.

#### Treatment

- Spray the bodywork (and clean rims if desired) from bottom to top with Cartec Wet & Protect. The product can be applied with a sprayer, a pressure pump or a foam lance. Dilute Wet & Protect 1:1 if a pressure pump is used, so that in the end 200-250 ml of pure product gets on the car. Make sure to touch all parts. Do not let the product dry on the surface.
- Then remove the Cartec Wet & Protect with a pressure washer. Rinse thoroughly again to further activate de product.
- Dry the surface with a Cartec Aqua Drying (3317/50) Towel XL or a chamois (3009/02) to prevent staining.

## Tips & Tricks:

- To avoid staining, always rinse Wet & Protect immediately after application and <u>do not let the product dry on the</u> <u>surface.</u>
- Never use Cartec Wet & Protect in full sunlight or in a hot environment.
- If necessary, apply Cartec Wet & Protect section by section in hot conditions.
- ✓ Cartec Wet & Protect contains silicone.
- ✓ When using the Cartec foam lance (3117/60), set it on position 2,5. (This for optimal consumption 200-250ml/ car at high-pressure cleaner consumption 11ltr/per minute).
- ✓ Using a pre-cleaner other than Cartec Twister Comfort may result in a negative effect on the final result.

# **Required items:**







#### Item codes:

ITEM CODE	CONTENT
1410/1	1L
1410/5	5L
1410/10	10L
1410/20	20L